

VERSIPANEL & PANELINK

INFORMATION SHEET

VERSIPANEL

Panel	Versipanel FC/FC		Versipanel OSB/FC		Versipanel OSB/OSB
Skins	6mm Fibre Cement		6mm Oriented Strand Board / 6mm Fibre Cement		6mm Oriented Strand Board
Thickness	103mm		103mm		103mm
Cover Width	900mm*	1200mm	900mm*	1200mm	1200mm
Length	3000mm	2400, 2700, 3000, 3600mm	3000mm	2400, 2700, 3000mm	2400, 2700, 3000mm
R _T Value Winter/Summer	2.5/2.4		2.5/2.4		2.6/2.5
Weight kg/m ₂	20.85		15		9.33

*900mm wide panels in 3000mm length only

PANELINK

Panel	Panelink Aluminium			Panelink Steel **			Rendapanel		
Skins	0.5mm Pre-Painted Aluminium			0.4mm Pre-Painted Steel			4.5mm Fibre Cement		
Thickness	38	50	75	38	50	75	38	50	75
Cover Width	1200mm			1140mm/1200mm			900^^ / 1200mm		1200mm
Length	2400, 2700, 3000, 3300mm, 3600mm			2400, 2700, 3000, 3300mm, 3600mm,			2400, 2700, 3000mm		2400, 2700, 3000mm
R _T Value Winter/Summer	1.1/1.1	1.4/1.3	2/1.9	1.1/1.1	1.4/1.3	2/1.9	0.9/0.9	1.2/1.2	1.8/1.7
Weight kg/m ₂	3.23	3.43	3.83	7.57	7.76	8.17	14.00	14.15	14.50

* Non-standard lengths available between 1200 & 8000mm with a minimum quantity of 4 panels required per non-standard length, or set up fee applies.

**Self-mating joint system

^^900mmwide panels available in 2400mm length only.