

Corrolink S 1000mm Cover Width

Minimum Fall: 3°

Versiclad STRUCTURAL INSULATED PANELS

Quote/Order Form

Date: / /	Order No.:	Job Name:
Company Name:		
Order Contact Name:	Order Contact Phone:	
Order Contact Email/Fax:		
Invoice Address:		
Delivery Address:		
Site Contact:	Site Contact Phone:	

1. Corrolink-S (1000mm) Quote / Order	Quote: <input type="checkbox"/>	Order: <input type="checkbox"/>
--	---------------------------------	---------------------------------

2. Thickness	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Core Thickness:	50mm	75mm	100mm	125mm	150mm	180mm
Overall Thickness:	67mm	92mm	117mm	142mm	167mm	197mm

3. Roof Colour

Off White <small>(*Surfmist)</small>	Smooth Cream <small>(*Classic Cream)</small>	Merino <small>(*Paperbark)</small>	Gull Grey <small>(*Shale Grey)</small>	Birch Grey <small>(*Dune)</small>	Armour Grey <small>(*Windspray)</small>	Slate Grey <small>(*Woodland Grey)</small>	Jasmin Brown <small>(*Jasper)</small>	Heritage Red <small>(*Manor Red)</small>	Mist Green <small>(*Pale Eucalypt)</small>	Unizinc <small>(*Zincalume)</small>

				+Limited Warranty					Corrosion Resistant Option	
Dusk <small>(*Evening Haze)</small>	Gulf <small>(*Gully)</small>	Wollaroo <small>(*Wallaby)</small>	Basal <small>(*Basalt)</small>							
				Mountain Blue+ <small>(Deep Ocean)</small>	Caulfield Green+ <small>(Cottage Green)</small>	Iron Grey+ <small>(Ironstone)</small>	Monolith+ <small>(Monument)</small>	Ebony+ <small>(Night Sky)</small>	MagnaFlow™ Off White <small>(*Surfmist)</small>	MagnaFlow™ Armour Grey <small>(*Windspray)</small>

*Equivalent colour names are trade marks or registered trade marks of BlueScope Steel Limited and used only for comparison. Colour and finish swatches are provided as an indication only and may not be an actual representation of colour or finish. We recommend checking your chosen colour and finish against an actual sample of the product before purchasing.

MagnaFlow™ only available with MagnaFlow™ ceiling skin.

4. Ceiling

Pearl White				Cream			Merino			^MagnaFlow™ Off White			^Timber Effect (Luxline only)
Smooth	Embossed	Micraline	Luxline	Smooth	Micraline	Luxline	Smooth	Micraline	Luxline	Smooth	Micraline	Luxline	Golden Oak

Only available with MagnaFlow™ top skin

^ Additional LM charge applies MagnaFlow & Timber Effect, refer pricelist.

5. Panel Quantities:

Quantity	@	Top Skin Length Min - 1500mm Max - 10000mm	Standard Configuration (viewed from gutter end): 60mm Gutter Cutback (Front only) / Right side Lap (Tick to select) <input checked="" type="checkbox"/>			Cover Width
			Alternatively, please nominate custom configuration below:			
			Gutter Cutback (Front) Specify Size (mm)	Cutback (Rear) Specify Size (mm)	Lap (Right or Left)	
	@				1000mm	
	@				1000mm	
	@				1000mm	
	@				1000mm	
	@				1000mm	
	@				1000mm	
	@				1000mm	

1. Flashings

Type	Roof Pitch	Style (please circle)	Colour	Qty.	Length (Max. 8m)	Qty.	Length (Max. 8m)
 Receiver Channel <i>(Please Specify Pitch)</i>		Stepped / Flush	White				
 Top End Capping <i>(Please Specify Pitch)</i>		Stepped / Crush Fold					
 Side Barge Capping	N/A	Stepped / Crush Fold					
 Z Gutter Fascia <i>(Please Specify Pitch)</i>		Stepped / Crush Fold					
 Ridge Capping <i>(Please Specify Pitch)</i>		N/A					
 Apron Flashing <i>(Please Specify Pitch)</i>		N/A					
Fire Flashing - Roof End x 1000mm (1 x req. per panel)			White				
Fire Flashing - Gutter End x 1000mm (1 x req. per panel)			White				

2. Gutter

Type	Colour	Qty.	Length
Square Gutter Slotted Square Gutter <i>(Max. 8m)</i>			
	Square Gutter Stop Ends (Pair)		
	Square Gutter Brackets		
Quad Gutter Slotted Quad Gutter 125 <i>(Max. 8m)</i>			
	Quad Gutter Stop Ends (Pair)		
	Quad Gutter External Brackets		
	Quad Gutter Internal Brackets	Galvanised	
	Quad Gutter External Corners		45 / 90° (Circle)
Quad Gutter Internal Corners	Galvanised		45 / 90° (Circle)

4. Screws

Length	Finish	Qty.	Painted Boxes	Colour (Boxes only)	Box Qty.
Metal Fix	110mm	Galv.		Box = 250	
	125mm	Galv.		Box = 250	
	150mm	Galv.		Box = 250	
	175mm	Galv.		Box = 250	
	205mm	Galv.		Box = 250	
	230mm	Galv.		Box = 250	
	250mm	Galv.		Box = 150	
Timber Fix	125mm	Galv.		Box = 250	
	150mm	Galv.		Box = 250	
	175mm	Galv.		Box = 250	
	200mm	Galv.		Box = 200	
	225mm	Galv.		Box = 200	
	250mm	Galv.		Box = 150	
300mm	Galv.		Box = 150		
Type	Colour	Qty.			
Stitching Screws Painted 16mm (100pk)					
Rivets Painted (100pk) 3.2mm dia. x 9.5mm grip					

3. Downpipes

Type	Colour	Qty.
Rectangle	Downpipe 2.4m - 100 x 50 Rect.	
	Downpipe Outlet - 100 x 50 Rect.	Galvanised
	Downpipe Straps - 100 x 50 Rect.	
	82° Offset - 100 x 50 Rect.	
Round	Downpipe 2.4m - 90mm Round	
	Downpipe Outlet - 90mm Round	Galvanised
	Downpipe Straps - 90mm Round	
	45° Bend - 90mm Round	

5. Accessories

Type	Details	Qty.
LED Downlight White Bezel, Dimmable	Multi: 3000/4000/5000k (Adjustable: Warm, Neutral, Cool)	
LED Downlight Brushed Aluminium Bezel, Dimmable	<i>(please circle)</i> Warm White (3000k) Cool White (5000k)	
Downlight Dimmer	Specialist LED	
Roof Infill Strip	Spacemaker x 1000mm	
Roof Infill Strip	Corrolink-S x 1000mm	
Roof Infill Strip	Versalink 1000 x 1000mm	
Eave / Ridge Filler Strip	Corrolink 915mm	
Eave Filler Strip	Versalink 765mm	
Ridge Filler Strip	Versalink 765mm	
Fan Fixing Plate <i>(inc. locking nut)</i>	White - 100mm Diameter	
Fan Fixing Plate Screws	1 x Profile Fix & 1 x Pan Fix	
Purlin Tape	5mm x 40mm - 13m Roll	
Butyl Tape	12mm x 15m Roll	
Touch Up Paint	Pearl White Spray Can 150gm	

1. Skylight Kit Combinations (Includes materials to install 1 x skylight per kit)

Type	Details	Qty.	Cut to Length (please specify length required)
Corrolink-S - 4m Kit	Top Fibreglass Strip Twinwall Bottom Diffuser Strip 2 x 4000mm T-Bars Foam Infill Strip Stormtite Stitching Screws Rivets Twinwall Sealer Tape		
Corrolink-S - 6m Kit	Top Fibreglass Strip Twinwall Bottom Diffuser Strip 2 x 6000mm T-Bars Foam Infill Strip Stormtite Stitching Screws Rivets Twinwall Sealer Tape		
Corrolink-S - 8m Kit	Top Fibreglass Strip Twinwall Bottom Diffuser Strip 4 x 4000mm T-Bars Foam Infill Strip Stormtite Stitching Screws Rivets Twinwall Sealer Tape		

Alternatively, you can order items required individually below:

2. Fibreglass Top & Twinwall Bottom

Type	Length	Qty.	Cut to Length (please specify length required)
Corrolink-S Top Fibreglass Strip	4m*		
	6m*		
	8m*		
Twinwall Diffuser Bottom Strip	4m*		
	6m*		
	8m*		

*Please note: you will be purchasing full lengths. We will cut these to your required lengths and you will be provided with any offcuts.

3. Accessories

Type	Qty.	Type	Qty.
Corrolink-S Foam Infill (Strip: 1 x per skylight)		Twinwall Sealer Tape (50m Roll)	
Rivets, White - 100 pack 3.2mm dia x 9.5mm		Stitching Screws - 50 pack Surfmist Storm-Tite 25mm	
Aluminium T-Bar White - 40 x 50mm	4m	Silicone: Clear/White (Please Circle)	
	6m		
Corrolink-S Accessory Bag: Foam Infill Strip 35 x Stormtite Stitching Screws 60 x Rivets 1m Twinwall Sealer Tape			

What you need:

- Fibreglass profiled top strip (4m, 6m & 8m only) - cut to match overall top sheet length, if required
- Twin wall bottom diffuser ceiling strip (4m, 6m & 8m only) - cut to match ceiling length, if required
- T-bar aluminium extrusions (4m & 6m only) - require 2 x T-Bars per light strip, either side of bottom diffuser strip
- Twin wall seal tape - require 460mm for each Skylight
- Foam infills (Spacemaker/Versalink 1000 = 2 piece set per skylight, Corrolink-S = 1 piece per skylight, cut to size onsite)
- Stormtite Screws - fixed through profile/crest at 600mm centres, along both sides of the fibreglass profiled top strip
- Blind Rivets - fixed through T-Bar at 300mm centres
- Silicone - run bead of silicone along top of horizontal section of T-Bar prior to pressing Twinwall into place and along Z Flashing prior to pressing foam infill into place

Please request and review engineering specifications prior to ordering skylights