

Signature Two Part Receiver Channel

With its separate top and base plates, the Signature Two Part Receiver Channel makes the process of interlocking Versiclad roof panels faster and easier on site.



Faster, easier panel installation

- The removable top plate simplifies the process of lapping and interlocking Versiclad insulated roof panels as the panel is not tightly wedged within the receiver as is the case with a folded receiver channel
- Adjustable top flap easily accommodates varying roof pitch angles
- Designated rear channel space for electrical wiring prevents wire crushing or damage from drilling
- Flexible hook-in or slide-in options for top plate caters to a variety of install scenarios
- Includes fastener positioning grooves to ensure straight lines and minimal slipping when drilling

Quality assured

- Made from structurally rigid, high-grade aluminium suitable for coastal regions
- Fire engineer approved for use in bushfire areas up to BAL-40



Signature Two Part Receiver Channel

Product Specifications

Maximum roof pitch*



Panel Thickness	Versalink 1000 (Min 1°)	Versalink 765 (Min 2°)	Spacemaker (Min 1°)	Corrolink 1000 (Min 3°)	Corrolink 765 (Min 5°)
50mm	5°	5°	2.5°	5°	5°
75mm	5°	5°	3°	5°	5°
100mm	5°	5°	3°	5°	5°

Panel thickness & Receiver suitability

Receiver Size	Versalink 1000 (Min 1°)	Versalink 765 (Min 2°)	Spacemaker (Min 1°)	Corrolink 1000 (Min 3°)	Corrolink 765 (Min 5°)
	Foam Thickness				
103x60x3	50mm	50mm	50mm	50mm	50mm
128x60x3	75mm	75mm	75mm	75mm	-
153x60x3	100mm	100mm	100mm	100mm	100mm

Thickness	Code	Description
50mm	RARC50/4.1i	Signature Aluminium Two Part Receiver Channel 50mm 4.1m
75mm	RARC75/4.1i	Signature Aluminium Two Part Receiver Channel 75mm 4.1m
100mm	RARC100/4.1i	Signature Aluminium Two Part Receiver Channel 100mm 4.1m
50mm	RARC50/6.1i	Signature Aluminium Two Part Receiver Channel 50mm 6.1m
75mm	RARC75/6.1i	Signature Aluminium Two Part Receiver Channel 75mm 6.1m
100mm	RARC100/6.1i	Signature Aluminium Two Part Receiver Channel 100mm 6.1m

* Two part receiver channel is not suitable for projects with a higher roof pitch listed in this table
 4.1m receivers are supplied with 2 x 2m Top plates and 2 x H Joiners
 6.1m receivers are supplied with 3 x 2m Top plates and 3 x H Joiners
 Available in Pearl White